

XG935H



| Description | | Unite | XG935H | |
|--------------|--|----------------|---|--|
| Engine | Brand | | Yuchai <input checked="" type="checkbox"/> | Cummins |
| | Model | | YC6J125Z-T20 | 6BTAA5.9-130 |
| | Type | | Four-stroke cycle, water-cooling, in line arrangement, direct-injection | Four-stroke cycle, water-cooling, in line arrangement, turbocharged air-air intercooled engine |
| | Cylinders-bore * Stroke | | 6-105*125 | 6-102*120 |
| | Rated power | kW | 92 | 97 |
| | Rated speed | rpm | 2200 | 2200 |
| | Max. torque | N.m | 500 | 580 |
| | Max. speed | r/min | 1500 | 1500 |
| | Fuel Consumption per hour | g/kW.h | ≤225 | ≤237 |
| Performance | Rated load | Kg | 3200 | |
| | Bucket capacity | m ³ | 1.4-3.0 | |
| | Operating weight | t | 10.8 | |
| | Max grade ability | ° | 28-30 | |
| | Discharge angle at full lift | ° | 45 | |
| | Dump clearance at full lift | mm | ≥3060(to cutting edge) | |
| | Dumping reach | mm | ≥1020 | |
| | Discharge angle | ° | ≥45 | |
| | Max. breakout force | KN | 100 | |
| | Lifting time of lift arm | S | ≤6.5 | |
| | Total Cycle time | S | ≤10.5 | |
| | Min turning radius (in carry position) | mm | 5860 | |
| | Overall dimensions (L*W*H) | mm | 6970*2245*3330 | |
| Travel Speed | Forward | I | Km/h | 0-12 |
| | | II | Km/h | 0-40 |
| | Reverse | Km/h | 0-16 | |

شركة ديبير للتجارة و الخدمات الوكيل الحصري لآليات اكسجاما في السودان

Address: Sudan - Khartoum - Altaif - Bshir Elnefeidi Street (Alsteen) - Block 3 - No 492
Tel: +249 9009 88888 - +249 1835 24908 Hot line: 2195 Email: info@deepertrading.com