

E-series



GB170EL

GB220EL

GB300EL

GB500EL

GB530EL- III

GB540EL

GB630EL

SPECIFICATIONS (E-Series)

Description		Unite	GB170E	GB220E	GB300E	GB500E	GB530E- III	GB540E	GB630E
Oil flow rate	lit/min		90~120	125~150	150~190	190~245	190~280	200~300	250~340
	gpm		24~32	33~40	40~50	50~65	50~74	53~79	66~90
Operating oil pressure	bar		160~180	160~180	160~180	160~180	160~180	160~180	160~180
	psi		2320~2610	2320~2610	2320~2610	2320~2610	2320~2610	2320~2610	2320~2610
Blows per minute	bpm		400~900	400~900	300~600	300~600	300~600	250~500	250~500
Impact Energy	Joule		2,800	4,800	6,000	9,000	10,500	12,000	13,700
	foot-pounds		2,065	3,540	4,425	6,638	7,744	8,850	10,104
Tool diameter	mm		120	135	150	160	165	175	180
	inch		4.72	5.31	5.90	6.30	6.50	6.89	7.10
Operating weight	Low noise box type with mounting cap	kg	1,120	1,750	2,200	3,200	3,360	3,780	4,600
		lb	2,464	3,850	4,840	7,040	7,407	8,330	10,141
	Side plate type with mounting cap	kg	1,280	1,820	2,390	3,150	3,240	3,620	4,550
		lb	2,816	4,004	5,258	6,930	7,128	7,980	10,030
Height with tool (without mounting cap, low noise box type)	mm		2,095	2,412	2,651	2,953	2,974	3,126	3,231
	inch		82.5	95	104.4	116.3	117	123	127
Weight of carrier	Min / Max	ton	13~20	18~26	25~32	30~36	35~40	38~45	45~70
		lbs	28,660~44,092	39,683~57,320	55,115~70,547	66,138~79,366	77,161~88,184	83,775~99,208	99,208~154,323
	Suitable	ton	17	21	28	35	40	45	50
		lbs	37,478	46,297	61,729	77,161	88,814	99,208	110,231
Bucket capacity	cbm		0.7~0.9	0.7~1.0	1.1~1.5	1.5~2.2	1.9~2.5	2.0~2.5	2.5~3.3

شركة ديبير للتجارة و الخدمات الوكيل المصري لجاك هامرات جي بي الكورية

Address: Sudan - Khartoum - Altaif - Bshir Elnefeidi Street (Alsteen) - Block 3 - No 492

Tel: +249 9009 88888 - +249 1835 24908 Hot line: 2195 Email: info@deepertrading.com

